

# MODEL 30-8

**\$4995**



## POWER CAVITY

- Brake: 6"
- Angle Shear
- Channel Shear
- Rod Shear (Round or Square)
- Z & T Shear

## PUNCH STATION

- Coper Notcher
- Pipe Notcher

<b>Throat Depth</b>	4 1/2"
<b>Tonnage</b>	30
<b>Punch</b>	3/4" hole in 1/2" 1 1/4" hole in 5/16"
<b>Bar Shear</b>	1/4" X 8" 1/2" X 6"
<b>Angle Shear 90°</b> - Server Cut	3" X 3" X 1/4"
<b>Miter Angle 45°</b> - Bar Shear	2" X 2" standard
<b>Channel Shear</b>	1" X 2" standard
<b>Rod Shear</b> - Round (max) - Square (max)	5/8" 5/8"
<b>Coper Notcher 90°</b>	For 3" X 3" X 1/4" angle
<b>Pipe Notcher</b> Sched 40 or 80	1/2", 3/4", 1", 1 1/4", 1 1/2", 1 3/4", 2"
<b>Brake</b>	6" x 1/4"
<b>Strokes per minute</b> - light material - at max capacity	9
<b>Hydraulics</b>	1,000 psi
<b>Oil Capacity</b>	15 quarts
<b>Motor</b> - Standard - Optional	3 HP, 3 phase 3 HP, 1 phase
<b>Dimensions</b> - Width - Length - Height	24" 27" 50"
<b>Weight (net)</b>	880 lbs.

## Accessories

- Punch nut wrench**
- Bar shear stop for production shearing to 24"**
- Grease bank for under cover lubrication**
- Punch Rack holds up to 30 sets of Punches & Dies**
- Steel bin catcher catches steel dropping from bar shear**
- Offset die stand for punching close to web \***

Please specify: size of angle to be punched, largest diameter hole to be punched and distance out from web to center of hole

## Features

- 8" Bar Shear with 4 Sided bar blades**
- Fixed or Adjustable bar shear hold-down**
- Forklift accommodations**
- Magnetic starter for safety and reliability**
- Sits flush with wall freeing up floor space**
- Rated for 65,000 PSI Tensile Mild Steel**
- Better designed for safety and durability**

## Tooling

- 6" Brake**
- Angle Shear**
- Channel Shear**
- Rod Shear**
- Coper Notcher**
- Pipe Notcher**

## Uni-Hydro, Inc

310 E Gemini Ave  
Cosmos, MN 56228  
800 - 328 - 0036