

# MODEL 5624

## 2° Low Rake ½" X 24" Flat Bar Shear

**\$9,995**

Forklift & Eyelet Accommodations



\* Shown with Optional Steel Bin Catcher  
\* & Optional Remote Foot Control

### Standard Equipment Includes

- 9" Punch Throat
- Manual Punch Aligner
- 4-Way 2° Low Rake 24" Flat Bar Shear
- 2¼" Stripper
- L100, 150 & 500 Series Punch & Die Adapter Kit that accepts up to 2¼" dia punching
- Variable Manual Stroke Control
- Flat Bar Shear Table
- Grease Bank
- 6" X 6" X 3/8" Angle Shear
- Available in 1 or 3 Phase

<b>Throat Depth</b>	9"
<b>Tonnage</b>	56
<b>Punch</b>	1 3/8" hole in ½" 2 ¼" hole in 5/16"
<b>Bar Shear</b>	½" x 24"
<b>Angle Shear 90°</b> - Slug Type - Sever Cut	6" x 6" x 3/8" 4" x 4" x 3/8"
<b>Miter Angle 45°</b> - Slug Type	4" x 4" x 3/8"
<b>Channel Shear</b>	2" & 3" combined 4" standard
<b>Rod Shear</b> - Round (max) - Square (max)	1 ¼" 1 ¼"
<b>Coper Notcher 90°</b>	4" x 4" x 3/8"
<b>Square Notcher</b>	3" x 3" x 3/8"
<b>Pipe Notcher</b> Sched 40 or 80	½", ¾", 1", 1 ¼", 1 ½", 2"
<b>Brake</b>	6", 9", 14", 18", 24" capacity
<b>Strokes per minute</b> - light material - at max capacity	50 9
<b>Hydraulics</b>	2,000 psi
<b>Oil Capacity</b>	16 gallons
<b>Motor</b> - Standard - Optional	5 HP, 3 phase 5 HP, 1 phase
<b>Dimensions</b> - Width - Length - Height - Bar shear work ht. - Punch table top ht. - Cavity table top ht.	37" 46" 70" 29" 39 ¼" 41"
<b>Weight (net)</b>	2,700 lbs

# New Model

## Uni-Hydro, Inc

310 E Gemini Ave  
Cosmos, MN 56228  
800 - 328 - 0036