

MODEL 80-24

\$15,500



** Shown with Optional Steel Bin Catcher*

Accessories

Choice of Punch nut wrench

Bar shear stop for production shearing to 24"

Grease bank for under cover lubrication

Punch Rack holds up to 30 sets of Punches & Dies

Steel bin catcher catches steel dropping from bar shear

Offset die stand for punching close to web *

Please specify: size of angle to be punched, largest diameter hole to be punched and distance out from web to center of hole

Throat Depth	9"
Tonnage	80
Punch	2" hole in 1/2" 1 3/8" hole in 3/4" 2 1/4" hole in 7/16"
Bar Shear	1/4" x 24" 1/2" x 20" 3/4" x 10" 1" x 6"
Angle Shear 90° - Bar Shear - Slug Type	6" x 6" x 1/2" 4" x 4" x 3/8"
Miter Angle 45° - Slug Type - Sever Cut	4" x 4" x 1/2" 4" x 4" x 3/8"
Channel Shear	2" & 3" combined 4", 5", 6" standard
Rod Shear - Round (max) - Square (max)	1 1/4" 1 1/4"
Coper Notcher 90°	4" x 4" x 1/2"
Square Notcher	3" x 3" x 3/8"
Pipe Notcher Sched 40 or 80	1/2", 3/4", 1", 1 1/4", 1 1/2", 2"
Brake	6", 9", 14", 18", 24" capacity
Strokes per minute - light material - at max capacity	50 9
Hydraulics	2,000 psi
Oil Capacity	16 gallons
Motor - Standard - Optional	7 1/2 HP, 3 phase 7 1/2 HP, 1 phase
Dimensions - Width - Length - Height - Bar shear work ht. - Punch table top ht. - Cavity table top ht.	37" 46" 70" 29" 39 1/4" 41"
Weight (net)	2,900 lbs

Uni-Hydro, Inc

310 E Gemini Ave

Cosmos, MN 56228

800 - 328 - 0036