

MODELS 135-24 AND 150-24

SPECIFICATIONS	MODELS 135-24	MODELS 150-24
Throat Depth	12" - 24"	12" - 24"
Punch	1 1/2" hole in 1" * 4" hole in 3/8"	1 7/8" hole in 1" * 4" hole in 7/16"
Bar Shear	1/2" x 24" 5/8" x 20" 3/4" x 18" 1" x 12"	1/2" x 24" 5/8" x 22" 3/4" x 18" 1" x 14"
Angle Shear 90° - Slug Type - Server Cut	6" x 6" x 1/2" 6" x 6" x 3/8"	6" x 6" x 1/2" 6" x 6" x 3/8"
Miter Angle 45° - Bar Shear - Slug Type	4" x 4" x 1/2" 4" x 4" x 3/8"	4" x 4" x 1/2" 4" x 4" x 3/8"
Channel Shear	2", 3", 4", 5", 6", 7", 8"	2", 3", 4", 5", 6", 7", 8"
Rod Shear - Round (max) - Square (max)	1 1/4" 1 1/4"	1 1/2" 1 1/2"
Coper Notcher 90° (notcher station) (punch or power cavity)	4" x 4" x 5/16" For 4" x 4" x 1/2"	4" x 4" x 5/16" For 4" x 4" x 1/2"
Square Notcher (notcher station) (punch or power cavity)	3" x 3" x 5/16" 3" x 3" x 3/8"	3" x 3" x 5/16" 3" x 3" x 3/8"
Pipe Notcher Sched 40 or 80 (larger sizes on request)	1/2", 3/4", 1", 1 1/4", 1 1/2", 2" larger available	1/2", 3/4", 1", 1 1/4", 1 1/2", 2" larger available
Brake	6", 9", 14", 18", 24" capacity	6", 9", 14", 18", 24" capacity
Strokes per minute - light material - at max capacity	40 8	40 8
Hydraulics	3,000 psi	3,000 psi
Oil Capacity	28 gallons	28 gallons
Motor - Standard - Optional	7 1/2HP, 3 phase 7 1/2HP, 1 phase	7 1/2 HP, 3 phase 7 1/2 HP, 1 phase
Dimensions - Width - Length - Height Bar shear work ht. Punch table top ht. Cavity tabletop ht Notcher station working ht.	46" 79" 91 1/2" 98" 32 1/2" 39" 43" 43"	46" 79" 91 1/2" 98" 32 1/2" 39" 43" 43"
Weight (net)	7,220 lbs	8,000 lbs