

MODELS T40-14 TO 56-14

SPECIFICATIONS	MODEL T40-14	MODEL 45-14	MODEL 56-14
Throat Depth	5 1/4"	6"	6"
Punch	1" hole in 1/2" 1 3/8" hole in 3/8"	1 1/8" hole in 1/2" 1 1/2" hole in 3/8"	1 1/4" hole in 1/2" 1 3/16" hole in 3/4"
Bar Shear	3/8" x 14" 1/2" x 10" 5/8" x 6"	3/8" x 14" 1/2" x 10" 5/8" x 6"	3/8" x 14" 1/2" x 10" 5/8" x 8" 3/4" x 6"
Angle Shear 90° - Slug Type - Sever Cut	3" x 3" x 3/8" 3" x 3" x 1/4"	3" x 3" x 3/8" 3" x 3" x 1/4"	3" x 3" x 3/8" 4" x 4" x 3/8"
Miter Angle 45° - Bar Shear - Slug Type	3" x 3" x 3/8" 2" x 2" x 5/16"	3" x 3" x 3/8" 2" x 2" x 5/16"	3" x 3" x 3/8" 2" x 2" x 5/16"
Channel Shear	1" & 2" combined or 3" standard	1" & 2" combined or 3" standard	2" & 3" combined 4" standard
Rod Shear - Round (max) - Square (max)	3/4" 3/4"	3/4" 3/4"	1 1/16" 1 1/16"
Coper Notcher 90°	For 3" x 3" x 1/4" angle	For 3" x 3" x 1/4" angle	For 3" x 3" x 1/4" angle
Square Notcher	1 3/4" x 2" x 1/4"	1 3/4" x 2" x 1/4"	1 3/4" x 2" x 1/4"
Pipe Notcher Sched 40 or 80	1/2", 3/4", 1", 1 1/4", 1 1/2"	1/2", 3/4", 1", 1 1/4", 1 1/2"	1/2", 3/4", 1", 1 1/4", 1 1/2", 2"
Brake	6" or 9" x 1/4"	6" or 9" x 1/4"	6" or 9" x 1/4"
Strokes per minute - light material - at max capacity	50 7	50 7	50 7
Hydraulics	1,000 psi	1,000 psi	1,200 psi
Oil Capacity	15 quarts	15 quarts	20 quarts
Motor - Standard - Optional	3 HP, 3 phase 3 HP, 1 phase	3 HP, 3 phase 3 HP, 1 phase	5 HP, 3 phase 5 HP, 1 phase
Dimensions - Width - Length - Height - Bar shear work ht. - Punch table top ht. - Cavity table top ht. - Notcher station working ht.	32" 46" 63 1/2" 30" 38 3/16" 37 1/4" --	28" 34" 60" 29" 38 1/4" 37 1/4" --	27 1/4" 33" 57" 29" 38 1/4" 37 1/4" --
Weight (net)	1,710 lbs.	1,240 lbs.	1,330 lbs

Uni-Hydro, Inc
310 E Gemini Avenue
Cosmos, MN 56228
1-800-328-0036